

PRIOR ART

PATENT ABSTRACTS OF JAPAN

Ref 2

(11)Publication number : 2002-265778

(43)Date of publication of application : 18.09.2002

(51)Int.Cl.

C08L 75/04
B65D 53/06
C08K 3/00
C08K 5/098
C09K 3/10

(21)Application number : 2001-066481

(71)Applicant : NIPPON POLYURETHANE IND CO
LTD

(22)Date of filing : 09.03.2001

(72)Inventor : YOKOTA HIROYOSHI

(54) SEALING MATERIAL FOR LID, COMPOSITION FOR FORMING LID- SEALING MATERIAL AND
MANUFACTURING METHOD FOR LID WITH SEALING MATERIAL USING THE SAME

(57)Abstract:

PROBLEM TO BE SOLVED: To obtain a sealing material for a lid excellent in sealing properties though permitting an opening operation by a weak power, a composition for forming a lid-sealing material, which permits to use a two-pack compounding apparatus for a main agent and a curing agent and further can be made into a one-pack composition when a blocked organic isocyanate is employed, and to provide a manufacturing method of a lid with a sealing material using the same.

SOLUTION: The composition for forming the sealing material for the lid comprises an optionally blocked organic isocyanate (a1), an active hydrogen group-containing compound (a2), inorganic powder (B), an organic lubricant (C) and a metallic soap (D). The manufacturing method of the lid with the sealing material comprises using this composition. The sealing material for the lid comprises a polyurethane resin (A), an inorganic powder (B), an organic lubricant (C) and a metallic soap (D).